

Rezeithow...

Werknorm

Gelenkbo...

6	hC	0	30	m6	+21 +8	Form A		4.
8	m6	+12 +6	40	m6	+9			5.
8	h8	0		m6	+25 +9	Form B		951
10	m6	-22 +15			+9			997
10	h8	0				Form B		1001
12	m6	+18 +7						1051
14	m6	+18 +7				Form B		1091
16	h8	0						1101
16	h8	-27 +18				Form B		1151
18	m6	+7						1201
20	m6	+6				Freimaßtoler...		1251
25	m6	+21 +8						1301

Type	d	l	c	r	Forml.	Typ	Typ	Typ	Typ	Typ	Typ	Typ	Typ	Typ
NM 021	8 m6	26.4	0.5	max.1.2	8	A	NM 090	100	100	100	100	100	100	100
NL 15							NL 60							
NM 031	10 m6	25	1.5	1.5	10	A	NM 100	100	100	100	100	100	100	100
NL 20							NL 100							
NL 25	12 m6	44		1.0			NL 100							
NM 038	8 h8	30		1.2	8	A	NM 320	10 h8	114					B
NL 30							NL 300							
NM 035	m6						NM 015							
NL 40														
NM 063	25 m6	78		4		A	NM 105							
NL 50														
NM 074	30	04		1.5	32	A		10	F2	15				
NL 60	30 m6	74		1.5	32	A		12 m6	63.2	1.6				A

KABUCO
Best. 01 18 71

Datum: 17.01.94
Bearb.: [Signature]
AL5- US. 74. 75. 76. 77. 78. 79. 80. 81. 82. 83. 84. 85. 86. 87. 88. 89. 90. 91. 92. 93. 94. 95. 96. 97. 98. 99. 100.